



▶ Desktop Keyboards

DP-72

Technical Specifications

Features and Benefits:

- ▶ Meets NEMA 4X Specifications
- ▶ Small-Footprint Design
- ▶ Extra Space Between Keys For Gloved-Hand Use
- ▶ Built-In Mounting Holes
- ▶ Color Arranged Keys
- ▶ Alphabetic Layout
- ▶ Industrial Silicone Keypad
- ▶ ABS Polycarbonate Case
- ▶ 10-Key Numeric Pad
- ▶ PS/2 or USB

INDUSTRIAL APPROVALS

NEMA 4, 4X
UL-1950, CE, FCC Class 15, Part B

KEY SWITCH

MATERIAL: Industrial silicone rubber
LIFE: Greater than 10 million cycles
TRAVEL: 0.050" (1.27mm)
ACTUATION FORCE: 5 oz (130g)
FEEDBACK: Tactile with mechanical snap

POWER

KEYBOARD: 5V@10ma (from CPU port)

TEMPERATURE RANGE

-40F to +194F (-40C to +90C)

HUMIDITY: 100%

SHOCK

3x11 ms pulses of 50g on each of 3 axes

FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2kHz
DURATION OF TEST PER AXIS: 3 hours

DIMENSIONS:

(W-H-D) 11.25" x 6.25" x 1.8"
285.75mm x 158.75mm x 45.72mm

CABLE

LENGTH: 3 feet (0.91 meters)
DESIGN: PS/2 or USB Cable

COMPATIBILITY

PS/2 KEYBOARD: All Windows Operating Systems
USB KEYBOARD: All Windows and Macintosh OS

WARRANTY: 1 Year Limited Warranty

MODEL NUMBERS:

DP-72-PS2: With PS/2 cable
DP-72-USB: With USB cable

