



▶ Desktop Keyboards

DPM-1000

Technical Specifications

Features and Benefits:

- ▶ 114-Key Functionality
- ▶ Meets NEMA 12 Specifications
- ▶ Lightweight Polycarbonate Case
- ▶ 24 Function Keys
- ▶ Industrial Membrane Keypad
- ▶ 10-Key Number Pad
- ▶ Suitable for 19-inch Rack Applications

Also Available:

Silicone Rubber Keypad : DP-1000
OEM: MEM-114-OEM

INDUSTRIAL APPROVALS

NEMA 4, 4X
UL-1950, CE, FCC Class 15, Part B

KEY SWITCH

MATERIAL: Industrial silicone rubber
LIFE: Greater than 10 million cycles
TRAVEL: 0.060" (1.5mm)
ACTUATION FORCE: 5 oz (130g)
FEEDBACK: Tactile with mechanical snap

POWER

KEYBOARD: 5V@10ma (from CPU port)

TEMPERATURE RANGE

-40F to +194F (-40C to +90C)

HUMIDITY: 100%

SHOCK

3x11 ms pulses of 50g on each of 3 axes

FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2kHz
DURATION OF TEST PER AXIS: 3 hours

DIMENSIONS:

(W-H-D) 15.5" x 8.0" x 1.5"
393.7mm x 203.2mm x 38.1mm

CABLE

LENGTH: 10 feet (3.94 meters)
DESIGN: "Y" PS2 or AT Cable (providing separate keyboard and mouse connections), or Single-Cable USB

COMPATIBILITY

PS/2: All Windows Operating Systems
USB: All Windows and Macintosh OS

WARRANTY: 1 Year Limited Warranty

MODEL NUMBERS:

DPM-1000-PS2: With PS/2 cable

DPM-1000-USB: With USB cable

DPM-1000-STD: With AT cable



© 2005 IKEY, Ltd.