



# ▶ Computer Pointing Devices

## DT-OM

### Technical Specifications

#### Features and Benefits:

- ▶ **AquaPoint™**
- ▶ Meets NEMA 4X Specifications
- ▶ Optical Tracking Technology
- ▶ Solid State Construction
- ▶ Industrial Silicone Overlay
- ▶ ABS Polycarbonate Frame
- ▶ Smooth Button Surface
- ▶ Comfortable, Ergonomic Design
- ▶ Available with USB or PS/2 Cables

#### INDUSTRIAL APPROVALS

NEMA 4X  
FCC Class 15, Part B, CE Rating, UL-1950

#### KEY SWITCH

MATERIAL: Industrial silicone rubber  
FEEDBACK: Tactile with mechanical snap

#### POWER

5V@50ma (from mouse conn. port)

#### TEMPERATURE RANGE

-40C to +90C

#### HUMIDITY: 100% Resistant

#### FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO  
SILICONE OVERLAY: 94 HB  
INTERFACE CABLE: 94 VO

#### WEIGHT

0.4 lb (0.18 kg)

#### DIMENSIONS

(W-H-D) 2.58" x 1.56" x 5"  
65.5mm x 39.7mm x 127mm

#### VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz  
FREQUENCY RANGE: 20Hz - 2kHz  
DURATION OF TEST PER AXIS: 3 hours

#### CABLE

LENGTH: 6 Feet  
DESIGN: PS/2 or USB cable

#### COMPATIBILITY

USB: All Windows and Mactintosh OS  
PS/2: All Windows Operating Systems

#### WARRANTY: 1 Year Limited Warranty

#### MODEL NUMBERS:

**DT-OM-PS2:** With PS/2 cable  
**DT-OM-USB:** With USB cable



© 2005 IKEY, Ltd.