

# ▶ Computer Pointing Devices



## DT-TB

## Technical Specifications

### Features and Benefits:

- ▶ Desktop Model
- ▶ Solid State Optical Technology
- ▶ Meets NEMA 4, 4X Specifications
- ▶ Removable Ball
- ▶ Adjustable Tension Ring
- ▶ Stainless Steel Case
- ▶ ESD Safe
- ▶ Left, Middle and Right Click
- ▶ Integrated Hand Support

### INDUSTRIAL APPROVALS

NEMA 4, 4X  
UL-1950, CE, FCC Class 15, Part B

### KEY SWITCH

MATERIAL: Industrial silicone rubber  
LIFE: Greater than 10 million cycles  
TRAVEL: 0.060" (1.5mm)  
ACTUATION FORCE: 5 oz (130g)  
FEEDBACK: Tactile with mechanical snap

### POWER

10ma (from mouse conn. port)

### TEMPERATURE RANGE

-40F to +194F (-40C to +90C)

**HUMIDITY:** 100%

### SHOCK

3x11 ms pulses of 50g on each of 3 axes

### FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO  
SILICONE OVERLAY: 94 HB  
INTERFACE CABLE: 94 VO

### VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz  
FREQUENCY RANGE: 20Hz - 2kHz  
DURATION OF TEST PER AXIS: 3 hours

### DIMENSIONS:

(W-H-D) 4.0" x 6.0" x 2.0"  
101.6mm x 152.4mm x 50.8mm

### CABLE

LENGTH: 10 feet (3.94 meters)  
DESIGN: PS/2 or USB Cable

### COMPATIBILITY

PS/2: All Windows Operating Systems  
USB: All Windows and Macintosh OS

**WARRANTY:** 1 Year Limited Warranty

### MODEL NUMBERS:

**DT-TB-PS2:** With PS/2 cable  
**DT-TB-USB:** With USB cable

### Also Available:

Panel Mount: PM-TB



© 2005 IKEY, Ltd.

**IKEY Industrial Peripherals**  
2621 Ridgepoint Drive, Suite 235  
Austin, TX 78754  
**1.800.866.6506**  
[www.ikey.com](http://www.ikey.com)