

▶ Computer Pointing Devices

PM-TB



Technical Specifications

Features and Benefits:

- ▶ Panel Mount Model
- ▶ Solid State Optical Technology
- ▶ Meets NEMA 4, 4X Specifications
- ▶ Removable Ball
- ▶ Adjustable Tension Ring
- ▶ Stainless Steel Bezel
- ▶ ESD Safe
- ▶ Left, Middle and Right Click

INDUSTRIAL APPROVALS

NEMA 4, 4X
UL-1950, CE, FCC Class 15, Part B

KEY SWITCH

MATERIAL: Industrial silicone rubber
LIFE: Greater than 10 million cycles
TRAVEL: 0.060" (1.5mm)
ACTUATION FORCE: 5 oz (130g)
FEEDBACK: Tactile with mechanical snap

POWER

10ma (from mouse conn. port)

TEMPERATURE RANGE

-40F to +194F (-40C to +90C)

HUMIDITY: 100%

SHOCK

3x11 ms pulses of 50g on each of 3 axes

FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2kHz
DURATION OF TEST PER AXIS: 3 hours

DIMENSIONS:

(W-H-D) 5.0" x 5.5" x 1.25"
127.0mm x 139.7mm x 31.75mm

CABLE

LENGTH: 10 feet (3.94 meters)
DESIGN: PS/2 or USB Cable

COMPATIBILITY

PS/2: All Windows Operating Systems
USB: All Windows and Macintosh OS

WARRANTY: 1 Year Limited Warranty

MODEL NUMBERS:

PM-TB-PS2: With PS/2 cable
PM-TB-USB: With USB cable

Also Available:

Desktop: DT-TB



© 2005 IKEY, Ltd.