



## ▶ Panel Mount Keyboards

# PMU-5K-TP

## Technical Specifications

### Features and Benefits:

- ▶ 116-Key Functionality
- ▶ Integrated HulaPoint™ Pointing Device
- ▶ Meets NEMA 4, 4X Specifications
- ▶ ABS Polycarbonate Frame
- ▶ 24 Function Keys
- ▶ Industrial Silicone Rubber Keypad
- ▶ 10-Key Number Pad
- ▶ MS Windows™ Key

### INDUSTRIAL APPROVALS

NEMA 4, 4X  
UL-1950, CE, FCC Class 15, Part B

### KEY SWITCH

MATERIAL: Industrial silicone rubber  
LIFE: Greater than 10 million cycles  
TRAVEL: 0.060" (1.5mm)  
ACTUATION FORCE: 5 oz (130g)  
FEEDBACK: Tactile with mechanical snap

### POWER

KEYBOARD: 5V@10ma (from CPU port)  
TOUCHPAD: 5V@5ma (from mouse conn. port)

### TEMPERATURE RANGE

-40F to +194F (-40C to +90C)

### HUMIDITY: 100%

### SHOCK

3x11 ms pulses of 50g on each of 3 axes

### FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO  
SILICONE OVERLAY: 94 HB  
INTERFACE CABLE: 94 VO

### VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz  
FREQUENCY RANGE: 20Hz - 2kHz  
DURATION OF TEST PER AXIS: 3 hours

### DIMENSIONS:

(W-H-D) 15.14" x 6.80" x 0.62"  
381.0mm x 165.1mm x 38.1mm  
CUTPIT: 13.36" x 5.03"

### CABLE

LENGTH: 10 feet (3.94 meters)  
DESIGN: "Y" PS/2 (providing separate keyboard and mouse connections)

### COMPATIBILITY

PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems

**WARRANTY:** 1 Year Limited Warranty

### MODEL NUMBERS:

**PMU-5K-PS2:** With PS/2 cable

### Also Available:

Desktop: DU-5K-TP



© 2005 IKEY, Ltd.

**IKEY Industrial Peripherals**  
2621 Ridgpoint Drive, Suite 235  
Austin, TX 78754  
1.800.866.6506  
www.ikey.com