



▶ Panel Mount Keyboards

PMU-5K

Technical Specifications

Features and Benefits:

- ▶ 116-Key Functionality
- ▶ Integrated HulaPoint™ Pointing Device
- ▶ Meets NEMA 4, 4X Specifications
- ▶ ABS Polycarbonate Frame
- ▶ 24 Function Keys
- ▶ Industrial Silicone Rubber Keypad
- ▶ 10-Key Number Pad
- ▶ MS Windows™ Key

INDUSTRIAL APPROVALS

NEMA 4, 4X
UL-1950, CE, FCC Class 15, Part B

KEY SWITCH

MATERIAL: Industrial silicone rubber
LIFE: Greater than 10 million cycles
TRAVEL: 0.060" (1.5mm)
ACTUATION FORCE: 5 oz (130g)
FEEDBACK: Tactile with mechanical snap

POWER

KEYBOARD: 5V@10ma (from CPU port)
HULAPOINT: 5V@10ma (from mouse conn. port)

TEMPERATURE RANGE

-40F to +194F (-40C to +90C)

HUMIDITY: 100%

SHOCK

3x11 ms pulses of 50g on each of 3 axes

FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2kHz
DURATION OF TEST PER AXIS: 3 hours

DIMENSIONS:

(W-H-D) 15.14" x 6.80" x 0.62"
381.0mm x 165.1mm x 38.1mm
CUTPIT: 13.36" x 5.03"

CABLE

LENGTH: 10 feet (3.94 meters)
DESIGN: "Y" PS/2 or AT/serial Cable
(providing separate keyboard and mouse connections), or Single-Cable USB

COMPATIBILITY

PS/2 KEYBOARD/HULAPOINT: All
Windows Operating Systems
USB KEYBOARD/HULAPOINT: All
Windows and Macintosh OS

WARRANTY: 1 Year Limited Warranty

MODEL NUMBERS:

PMU-5K-PS2: With PS/2 cable
PMU-5K-USB: With USB cable
PMU-5K-STD: With AT/serial cable

Also Available:

Desktop: DU-5K



© 2005 IKEY, Ltd.