

## P50 standard - ABCDEF product ordering code

Please fill in the letters A to F using the numbers from the table below.

|          | Options                | Code     | Description   |
|----------|------------------------|----------|---|
| <b>A</b> | Top Plate Sealing      | <b>1</b> | No seal in top plate, IP40/NEMA   |
|          |                        | <b>2</b> | PTFE scraper seal in top plate, IP51/NEMA                               |
|          |                        | <b>4</b> | PTFE seal, IP54/NEMA  |
|          |                        | <b>5</b> | PTFE seal, IP65/NEMA  |
| <b>B</b> | Electrical Output      | <b>0</b> | Quadrature  |
|          |                        | <b>6</b> | Universal interface - PS/2, USB   |
|          |                        | <b>A</b> | RS232 only  |
|          |                        | <b>8</b> | Sun Systems   |
| <b>C</b> | Integrated Switches    | <b>0</b> | No switches   |
| <b>D</b> | Mounting               | <b>2</b> | Mount to back of panel  |
| <b>E</b> | Top Plate / Body Style | <b>0</b> | Stainless Steel overflange mounted to top plate, sealing ring, black    |
|          |                        | <b>3</b> | Moulded top & chassis (sealed format), black                            |
|          |                        | <b>4</b> | Moulded top & chassis (no seal), black                                  |
| <b>F</b> | Ball Colour            | <b>0</b> | Black   |
|          |                        | <b>4</b> | Yellow  |
|          |                        | <b>8</b> | Stainless steel (316)   |
|          |                        | <b>9</b> | Backlit option  |
|          |                        | <b>C</b> | Stainless steel (440)   |
|          |                        |          | Alternative ball colours and backlit options are available upon request |