

## models **include:**



### **DT-5K-MEM-TP**

Desktop Model in Stainless Steel Case  
412.8mm x 200.2mm x 45.7mm (w-h-d)



### **PM-5K-MEM-TP**

Panel Mount Model in Stainless  
Steel Bezel  
449.6mm x 233.7mm x 38.1mm (w-h-d)  
Mounting Cutout: 416.6mm x 200.7mm



### **KYB-5K-MEM-TP-OEM**

OEM Kit  
382.3mm x 166.4mm (w-h)  
Panel Cutout: 360.7mm x 144.8mm

## technical **specifications:**

### **MATERIAL**

Hardcoated, Textured Polyester Film

### **POWER**

PS2: KEYBOARD: 40mA@5V (Keyboard port)  
TOUCHPAD: 10mA@5V (Mouse port)  
USB: 50mA@5V(CPU port)

### **TEMPURATURE RANGE**

STORAGE : -40F to +149F (-40C to +65C)  
OPERATING: 32F TO 140F (0C TO 60C)

### **CERTIFICATIONS**

MEETS OR EXCEEDS:  
NEMA 4X, IP67  
UL60950  
FCC, Part 15, Class B  
CE

### **SHOCK**

3 x 11 ms pulses of 50g on each of 3 axes

### **VIBRATION**

POWER SPECTRAL DENSITY: .04g/HZ  
FREQUENCY RANGE: 20 Hz-2Khz  
DURATION OF TEST PER AXIS: 3 hours

### **CABLE**

LENGTH: 10 feet (3.94 meters)  
DESIGN: "Y" PS/2 Cable (providing separate keyboards and mouse connections), or Single-Cable USB

### **COMPATIBILITY**

PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems  
USB KEYBOARD/TOUCHPAD: All Windows and Macintosh OS

### **KEY DATA**

LIFE: Greater Than 2 Million Cycles  
TRAVEL: 0.020 in. (Positively effected by Trampoline Mounting™)  
ACUATION FORCE: 9.88 oz +/- 1.06 oz (280g +/- 30g)  
FEEDBACK: Tactile with Mechanical Snap

### **HUMIDITY**

100%

### **WARRANTY**

1 Year Limited Warranty

Patents pending.