

SK-97-TP

Main Features

- Cleanable, Liquidproof Design
- Integrated Touchpad
- 12 Function Keys + 10-Key Numeric Pad
- Rugged ABS Case
- Various Keyboard and Language Layout Options



Typical Applications

- Commercial
- Emergency Services
- Field Services
- Healthcare
- Industrial
- Medical
- Mobile Work force

Product Description

iKey's SK-97-TP medical keyboard provides users with all the functionality of a full-size keyboard and mouse in a slim, compact package. It is designed for infection control in today's healthcare environment including Hospitals, Laboratories, Clinics, Dentists as well as for industrial applications.

The fully sealed keyboard has an integrated touchpad and is compatible with all hospital and Dental approved disinfectants. With higher-profile keys than the FL-series medical keyboards, the SK-97-TP has a more responsive and tactile feel. It features left and right-click buttons below the touchpad, adding convenience and functionality. The durable and easily cleanable SK-97-TP and is ideal for use in ORs, medical carts and industrial workstations.



Technical Specifications

SKU	SK-97-TP
Manufacturer	iKey
Country of Manufacture	United States
IP Rating	No
Number Of Keys	97
Function Keys	12 Keys
Key Material	Silicone Rubber
Pointing Device	Touchpad
Backlight	No Backlight
Case Material	ABS Polycarbonate
Interface Options	PS2, USB
Shock	3 x 11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10ft (3m)
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS/2: KEYBOARD: 50mA@5V (from Keyboard port) TOUCHPAD: 10 mA@5V (from Mouse port) USB: 60mA@5V (from CPU port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB INTERFACE CABLE: 94 VO
Compatibility	PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems USB KEYBOARD/TOUCHPAD: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
Weight	1.5 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)
Warranty	1 Year Limited Warranty
Humidity	100% Humidity Resistant
Dimensions	(w-h-d) 366.8mm x 137.2mm x 22.6mm
Certifications	IP Rated, NEMA 4X, CE UL60950, FCC Part 15 Class B
Model Number(s)	SK-97-TP-PS2: With PS/2 Cable

SK-97-TP-USB: With USB Cable

SK-97-TP-USB: With USB Cable

