

SL-86-911-TP-FL

Main Features

- 86-Key Functionality
- Integrated Touchpad
- One-Touch Emergency Key
- Red LED Backlighting
- Various Keyboard and Language Layout Options

Typical Applications

- Commercial
- Emergency Services
- Field Services
- Industrial
- Mobile Work force



Product Description

The SL-86-911-TP-FL keyboard is designed for in-vehicle use for emergency, police, service, transport trucks and marine vessels. Its thinner depth dimension of 1.125 inches allows it to fit easily into existing mounts.

Features include a user-friendly integrated touchpad, backlit keys for low-light environments, a one-touch emergency key. The new, easy-to-use integrated touchpad was created to meet public demand for a user-friendly alternative to the traditional HulaPoint™ pointing device.



Technical Specifications

SKU	SL-86-911-TP-FL
Manufacturer	iKey
Country of Manufacture	United States
IP Rating	No
Number Of Keys	86
Function Keys	10 Keys
Key Material	Silicone Rubber
Pointing Device	Touchpad
Backlight	Red
Case Material	ABS Polycarbonate
Interface Options	PS2, USB
Shock	3 x 11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 4 ft coiled (1.2m) DESIGN: ??????????????????????Y???? ?????????????? PS/2 (providing separate keyboard and mouse connections), or Single-Cable USB
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	KEYBOARD: 200mA@5V (from Keyboard port) TOUCHPAD: 10mA@5V (from mouse port) USB: 210mA@5V (from CPU port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB INTERFACE CABLE: 94 VO
Compatibility	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
Weight	2 lbs +/- 0.10 lbs (1.38 kg +/- 0.05 kg)
Warranty	1 Year Limited Warranty
Humidity	100% Humidity Resistant
Dimensions	12.0" x 7.74" x 1.27" (w-h-d) 304.8mm x 196.6mm x 32.3mm
Certifications	NEMA 4X UL60950, FCC Part 15 Class B

Model Number(s)

SL-86-911-TP-FL-PS2: With PS/2 cable SL-86-911-TP-FL-USB: With USB cable
