



SLK-102-TP

Main Features

- Low-Profile Keys For Easy Cleaning
- Integrated Touchpad
- Integrated LED Backlighting
- Low-Profile Keys For Easy Cleaning
- Various Keyboard and Language Layout Options

Typical Applications

- Commercial
- Field Services
- Healthcare
- Industrial
- Medical
- Mobile Work force



Product Description

iKey's SlimKey™ SLK-102-TP keyboard provides full-size versatility in a rugged, compact design, with the added convenience of an integrated touchpad. It features red LED backlit keys for use in areas with minimal lighting.

The SlimKey™ SLK-102-TP is engineered to meet NEMA 4X specifications and is ideal for use in industrial, medical and material handling applications. The large numeric pad on the SLK-102-TP allows for easy data entry, while the robust polycarbonate case is durable in the roughest of environments.



Technical Specifications

SKU	SLK-102-TP
Manufacturer	iKey
Country of Manufacture	United States
IP Rating	No
Number Of Keys	102
Function Keys	12 Keys
Key Material	Silicone Rubber
Pointing Device	Touchpad
Backlight	Red
Case Material	ABS Polycarbonate
Interface Options	PS2, USB
Shock	3 x 11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 and Serial Cable (providing separate keyboard and mouse connections), or Single-Cable USB
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS2: KEYBOARD: 210mA@5V (from Keyboard port) TOUCHPAD: 10mA@5V (from Mouse port) USB: 220mA@5V (from CPU port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB INTERFACE CABLE: 94 VO
Compatibility	KEYBOARD: PS/2: All Windows Operating Systems; USB: All Windows and Macintosh OS TOUCHPAD: PS/2: All Windows Operating Systems; USB: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +65C (-40F to +149F) OPERATING: 0C to +60C (+32F to +140F)
Weight	1.5 lbs +/- 0.10 lbs (0.91 kg +/- 0.05 kg)
Warranty	1 Year Limited Warranty
Humidity	100% Humidity Resistant
Dimensions	14.60" x 5.55" x 0.91" (w-h-d) 370.8mm x 141mm x 23.1mm
Certifications	IP Rated, NEMA 4X UL60950, FCC Part 15 Class B
Model Number(s)	SLK-102-TP-PS2: With PS/2

cable
SLK-102-TP-USB: With USB cable
