

SLK-77

Main Features

- Ultra-Small Footprint Design
- Industrial Silicone Rubber Keypad
- Red LED Backlighting
- USB Configurations Available
- Various Keyboard and Language Layout Options

Typical Applications

- Commercial
- Industrial



Product Description

The compact SLK-77 keyboard is packed with functionality. It features a full QWERTY keyboard layout, 12 function keys, and red LED backlighting in a rugged ABS polycarbonate case measuring 9.27" x 3.87" (width-height).

The SLK-77 is designed to meet NEMA 4X specifications, with a completely sealed industrial silicone rubber keypad that can withstand the dirt, dust, water and corrosives that often exist in harsh environments. It is an excellent keyboard for material handling, mobile and industrial applications.



 iKey

Technical Specifications

SKU	SLK-77
Manufacturer	iKey
Country of Manufacture	United States
IP Rating	No
Number Of Keys	77
Function Keys	12 Keys
Key Material	Silicone Rubber
Pointing Device	No Pointer
Backlight	Red
Case Material	ABS Polycarbonate
Interface Options	PS2, USB
Shock	3 x 11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 3' straight (0.91 m) DESIGN: Single Cable USB
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	USB: 200mA@5V (from CPU port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB INTERFACE CABLE: 94 VO
Compatibility	USB: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
Weight	1.00 lbs +/- 0.10 lbs (0.45 kg +/- 0.05 kg)
Warranty	1 Year Limited Warranty
Humidity	100% Humidity Resistant
Dimensions	9.27" x 3.87" x 0.90" (w-h-d) 235.5mm x 98.3mm x 22.9mm
Certifications	IP Rated, NEMA 4X, CE UL60950, FCC PART 15 CLASS B
Model Number(s)	SLK-77-USB: With USB Cable