



SLK-79-M

Main Features

- Compact Mobile Keyboard
- Integrated HulaPoint Pointing Device
- Red LED Backlighting
- USB and PS2 Configurations Available
- Various Keyboard and Language Layout Options

Typical Applications

- Commercial
- Field Services
- Industrial
- Mobile Work force

Product Description

The SLK-79-M has been designed for those mobile applications when a small-footprint keyboard may come in handy. Featuring an integrated HulaPoint IITM pointing device with dual left-click capability, the SLK-79-M offers a large amount of functionality in an ultra-small package.

For working in low-light environments, the SLK-79 features the added convenience of backlit keys. Like other keyboards in the iKey line, the SLK-79-M features sealed industrial silicone rubber keypads, as well as robust ABS polycarbonate cases. The SLK-79-M features mounting holes in its case.



Technical Specifications

SKU	SLK-79-M
Manufacturer	iKey
Country of Manufacture	United States
IP Rating	No
Number Of Keys	79
Function Keys	10 Keys
Key Material	Silicone Rubber
Pointing Device	HulaPoint
Backlight	Red
Case Material	ABS Polycarbonate
Mounting Options	VESA
Interface Options	PS2, USB
Shock	3 x 11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 3 feet (0.91 meters) DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections), or Single-Cable USB
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS/2: KEYBOARD: 200mA@5V (from Keyboard port) POINTER: 35mA@5V (from Mouse port) USB: 235mA@5V (from CPU port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB INTERFACE CABLE: 94 VO
Compatibility	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)
Weight	1 lbs +/- 0.10 lbs (0.45 kg +/- 0.05kg)
Warranty	1 Year Limited Warranty
Humidity	100% Humidity Resistant
Dimensions	9.31" x 3.88" x 1.68" (w-h-d) 236.5mm x 98.6mm x 42.7mm
Certifications	IP Rated, NEMA 4X, CE UL60950, FCC Part 15 Class B

Model Number(s)

SLK-79-M-PS2: With PS/2
cable

SLK-79-M -USB: With USB cable
