

SLP-91

Main Features

- 24 Function Keys
- Integrated 10-Key Numeric Pad
- Integrated LED Backlighting
- USB and PS2 Configurations Available
- Various Keyboard and Language Layout Options

Typical Applications

- Commercial
- Industrial
- OEM
- System Integrators



Product Description

iKey's innovative SLP-91 panel mount keyboard was designed to accommodate rugged applications in manufacturing, material handling and data entry. Its unique epoxy-coated keys are arranged for convenient gloved-hand use.

It features a small-footprint design, backlit keys and a 10-key numeric pad. Like other keyboards in the iKey line, the SLP-91 is constructed with an industrial silicone keypad, sealing it from dust, liquids and corrosives.



Technical Specifications

SKU	SLP-91
Manufacturer	iKey
Country of Manufacture	United States
IP Rating	No
Number Of Keys	91
Function Keys	24 Keys
Key Material	Epoxy
Pointing Device	No Pointer
Backlight	Red
Case Material	ABS Polycarbonate
Interface Options	PS2, USB
Shock	3 x 11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 4 ft coiled (1.2m) DESIGN: PS/2 or USB Cable
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS/2: KEYBOARD: 200mA@5V (from Keyboard port) USB: 200mA@5V (from CPU port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB INTERFACE CABLE: 94 VO
Compatibility	PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
Weight	1.75 lbs (0.80 kg)
Warranty	1 Year Limited Warranty
Humidity	100% Humidity Resistant
Dimensions	11.80" x 6.79" x 0.70" (w-h-d) 299.7mm x 172.5mm x 17.8mm SCREWS: 0.75" (19.1mm) CUTOUT: 10.40" x 5.40" (w-h) 264.2mm x 137.2mm
Certifications	IP Rated, NEMA 4X UL60950, FCC Part 15 Class B
Model Number(s)	SLP-91-PS2: With PS/2 cable

SLP-91-USB: With USB cable

