



## SLK-97-TP

### Main Features

- Cleanable, Liquidproof Design
- Integrated Touchpad
- 12 Function Keys + 10-Key Numeric Pad
- Rugged ABS Case
- Red LED Backlighting



### Typical Applications

- Commercial
- Emergency Services
- Healthcare
- Industrial
- Medical

## Product Description

---

IKey's SLK-97-TP keyboard provides users with all the functionality of a full-size keyboard and mouse in a slim, compact package. It is designed for infection control in today's healthcare environment and for industrial applications.

The fully sealed keyboard has an integrated touchpad and is compatible with all hospital-approved disinfectants. It is manufactured with red LED backlighting for use in low-light environments. The SLK-97-TP features left and right-click buttons below the touchpad, adding convenience and functionality. The durable and easily cleanable SLK-97-TP is ideal for use in ORs, medical carts and industrial workstations.

## Technical Specifications

---

<b>SKU</b>	slk-97-tp
<b>Manufacturer</b>	iKey
<b>Country of Manufacture</b>	United States
<b>IP Rating</b>	No
<b>Function Keys</b>	12 Keys
<b>Key Material</b>	Silicone Rubber
<b>Pointing Device</b>	Touchpad
<b>Backlight</b>	Red
<b>Case Material</b>	ABS Polycarbonate
<b>Interface Options</b>	USB
<b>Shock</b>	3 x 11 ms pulses of 50g on each of 3 axes
<b>Cable</b>	LENGTH: 10ft (3m)
<b>Vibration</b>	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
<b>Power</b>	PS/2: KEYBOARD: 50mA@5V (from Keyboard port) TOUCHPAD: 10 mA@5V (from Mouse port) USB: 60mA@5V (from CPU port)
<b>Flammability</b>	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB INTERFACE CABLE: 94 VO
<b>Compatibility</b>	PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems USB KEYBOARD/TOUCHPAD: All Windows and Macintosh OS
<b>Temperature Range</b>	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
<b>Weight</b>	1.5 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)
<b>Warranty</b>	1 Year Limited Warranty
<b>Humidity</b>	100% Humidity Resistant
<b>Dimensions</b>	14.44x 5.40x 0.89 (w-h-d) 366.8mm x 137.2mm x 22.6mm
<b>Certifications</b>	IP Rated, NEMA 4X, CE UL60950, FCC Part 15 Class B
<b>Model Number(s)</b>	SK-97-TP-PS2: With PS/2 Cable SK-97-TP-USB: With USB Cable SK-97-TP-USB: With USB Cable