

## SLP-102-FSR

### Main Features

- Cleanable, Liquidproof Design
- Integrated Force Sensing Resistor
- Red LED Backlighting
- ABS Polycarbonate Frame
- Various Keyboard and Language Layout Options

### Typical Applications

- Commercial
- Industrial
- OEM
- System Integrators



## Product Description

---

iKey's SlimKey SLP-102 panel mount keyboard provides full-size versatility in a rugged, compact design with the added convenience of an integrated Force Sensing Resistor (FSR) pointing device. It features red LED backlighting for easy use in areas with minimal lighting. When properly installed, the SlimKey™ SLP-102 is engineered for NEMA 4X protection against dust, water and corrosive liquids. It is designed for easy integration into workstations, kiosks and industrial environments. The large numeric pad on the SLP-102 allows for easy data entry, while the robust polycarbonate case is durable in the roughest of environments.

## Technical Specifications

---

<b>SKU</b>	SLP-102-FSR
<b>Manufacturer</b>	iKey
<b>Country of Manufacture</b>	United States
<b>IP Rating</b>	No
<b>Number Of Keys</b>	102
<b>Function Keys</b>	12 Keys
<b>Key Material</b>	Silicone Rubber
<b>Pointing Device</b>	Force Sensing Resistor
<b>Backlight</b>	Red
<b>Interface Options</b>	PS2, USB
<b>Shock</b>	3 x 11 ms pulses of 50g on each of 3 axes
<b>Cable</b>	Single-Cable USB
<b>Vibration</b>	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
<b>Power</b>	PS2: KEYBOARD: 210mA@5V (from Keyboard port) POINTER: 35mA@5V (from Mouse port) USB: 245mA@5V (from CPU port)
<b>Flammability</b>	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB INTERFACE CABLE: 94 VO
<b>Compatibility</b>	All Windows and Macintosh Operating Systems
<b>Temperature Range</b>	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
<b>Weight</b>	1.50 lbs (0.68 kg)
<b>Warranty</b>	1 Year Limited Warranty
<b>Humidity</b>	100% Humidity Resistant
<b>Dimensions</b>	15.10" x 6.05" x 0.59" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50 (12.7mm) CUTOUT: 13.70" X 4.65" (w-h) 348mm x 118.1mm
<b>Certifications</b>	IP Rated, NEMA 4X, CE UL 60950, FCC Part 15 Class B
<b>Model Number(s)</b>	SLP-102-FSR