



DM-0651-C2

Main Features

- Integrated Control Panel
- OSD With Multi-Language Support
- Wall Mount VESA Compliant (75 x 75 mm)
- Integrated Stereo Speakers

Typical Applications

- Aerospace
- Commercial
- Defence
- Industrial Consoles
- Marine Consoles
- Medical Systems
- Military
- OEM
- Radar Applications
- System Integrators



Product Description

The DM-0651-C2 6.5" Chassis TFT LCD Display has a host of features including OSD With Multi-Language Support ,Wall Mount VESA Compliant (75 x 75 mm),Integrated Stereo Speakers to name a few. Designed and built to survive harsh conditions and are perfectly suited for Aerospace , Commercial , Defence , Industrial Consoles , Marine Consoles , Medical Systems , Military , OEM , Radar Applications , System Integrators and other demanding applications. The typical lifetime of an DM-0651-C2 6.5" Chassis TFT LCD Display is approximately 50,000 hours (typ).

Technical Specifications

SKU	DM-0651-C2
Weight	2.0000
Manufacturer	FBP
Country of Manufacture	Taiwan
Screen size	6.5"
Mounting Type	No
IP Rating	No
Screen Technology	LCD
Aspect Ratio	04:03
Display Resolution	640 x 480
Backlight Life	50,000 hours (typ)
Viewing Angle	140 degree in horizontal & 120 in vertical (typ)
Frequency Range	Fh: 30 to 82Khz, Fv: 60 to 75Hz
Brightness	400 cd/m2
Response Time	< 25 ms
Contrast Ratio	500:01:00
Pixel Dimension	0.207 (H) x 0.207 (V) mm
OSD Control	No
Connectivity	15 Pin female D-Sub x 1, Stereo headphone jack x 1, 12 VDC jack
Video Signal	Analog RGB (0.7/1.0 Vp-p, 75 ohms)
Sync. Signal	Separate Sync, Composite Sync, Sync on Green
Power - Input Voltage	Universal/ Auto-sensing, 90 to260V AC, 50/60 Hz
Power Consumption	Operation 12 Watt (Max), Stand-by < 2 Watt
Temperature Range	OPERATING: 0C to +40C / STOREAGE: -20C to +60C
Dimensions	176.6 (L) x 132.6 (W) x 49.2 (D) mm
Weight	2.0 Kg (N.W.) / 3.0 Kg (G. W.)
Certifications	CE
Accessories Included	AC/DC Power Adapter

Model Number(s)	DM-0651-C2
Warranty	1 Years RTB Warranty
Availability	3-5 Weeks
