



DM-1205D-S-L

Main Features

- Integrated Control Panel
- OSD With Multi-Language Support
- Wall Mount VESA Compliant (75 x 75 mm)
- Integrated Stereo Speakers

Typical Applications

- Aerospace
- Commercial
- Defence
- Industrial Consoles
- Marine Consoles
- Medical Systems
- Military
- OEM
- Radar Applications
- System Integrators

Product Description

The DM-1205D-S-L 12" Digital Signage LCD Display has a host of features including OSD With Multi-Language Support ,Wall Mount VESA Compliant (75 x 75 mm),Integrated Stereo Speakers to name a few. Designed and built to survive harsh conditions and are perfectly suited for Aerospace , Commercial , Defence , Industrial Consoles , Marine Consoles , Medical Systems , Military , OEM , Radar Applications , System Integrators and other demanding applications. The typical lifetime of an DM-1205D-S-L 12" Digital Signage LCD Display is approximately 50,000 hours (typ).



Technical Specifications

SKU	DM-1205D-S-L
Weight	3.0000
Manufacturer	FBP
Country of Manufacture	Taiwan
Screen size	12"
Mounting Type	No
IP Rating	No
Screen Technology	LCD
Aspect Ratio	04:03
Display Resolution	1024 x 768
Backlight Life	50,000 hours (typ)
Viewing Angle	140 degree in horizontal & 120 in vertical (typ)
Brightness	200 cd/m2
Response Time	< 25 ms
Contrast Ratio	400:01:00
Pixel Dimension	0.24 (H) x 0.24 (V) mm
OSD Control	No
Power - Input Voltage	Universal/ Auto-sensing, 90 to260V AC, 50/60 Hz
Power Consumption	Operation: 22 Watt (Max) Stand-by < 5 Watt
Temperature Range	OPERATING: 0C to +40C / STORAGE: -20C to +60C
Weight	3.0 Kg (N.W.) / 4.0 Kg (G. W.)
Certifications	CE
Accessories Included	AC/DC Power Adapter
Model Number(s)	DM-1205D-S-L
Warranty	1 Years RTB Warranty
Availability	3-5 Weeks