

## DM-1508D-S-L

### Main Features

- Integrated Control Panel
- OSD With Multi-Language Support
- Wall Mount VESA Compliant ( 75 x 75 mm)
- Integrated Stereo Speakers

### Typical Applications

- Aerospace
- Commercial
- Defence
- Industrial Consoles
- Marine Consoles
- Medical Systems
- Military
- OEM
- Radar Applications
- System Integrators



## Product Description

---

The DM-1508D-S-L 15" Digital Signage LCD Display has a host of features including OSD With Multi-Language Support ,Wall Mount VESA Compliant ( 75 x 75 mm),Integrated Stereo Speakers to name a few. Designed and built to survive harsh conditions and are perfectly suited for Aerospace , Commercial , Defence , Industrial Consoles , Marine Consoles , Medical Systems , Military , OEM , Radar Applications , System Integrators and other demanding applications. The typical lifetime of an DM-1508D-S-L 15" Digital Signage LCD Display is approximately 50,000 hours (typ).



## Technical Specifications

---

<b>SKU</b>	DM-1508D-S-L
<b>Weight</b>	4.0000
<b>Manufacturer</b>	FBP
<b>Country of Manufacture</b>	Taiwan
<b>Screen size</b>	15"
<b>Mounting Type</b>	No
<b>IP Rating</b>	No
<b>Screen Technology</b>	LCD
<b>Aspect Ratio</b>	04:03
<b>Display Resolution</b>	1024 x 768
<b>Backlight Life</b>	50,000 hours (typ)
<b>Viewing Angle</b>	130 degree in horizontal & 100 in vertical (typ)
<b>Brightness</b>	250 cd/m2
<b>Response Time</b>	< 12 ms
<b>Contrast Ratio</b>	450:01:00
<b>Pixel Dimension</b>	0.297 (H) x 0.297 (V) mm
<b>OSD Control</b>	No
<b>Power - Input Voltage</b>	Universal/ Auto-sensing, 90 to260V AC, 50/60 Hz
<b>Power Consumption</b>	Operation: 20 Watt ( Max ) Stand-by < 2 Watt
<b>Temperature Range</b>	OPERATING: 0C to +40C / STORAGE: -20C to +60C
<b>Weight</b>	4.0 Kg (N.W.) / 5.0 Kg (G. W.)
<b>Certifications</b>	CE
<b>Accessories Included</b>	AC/DC Power Adapter
<b>Model Number(s)</b>	DM-1508D-S-L
<b>Warranty</b>	1 Years RTB Warranty
<b>Availability</b>	3-5 Weeks