



DM-15W2-OF

Main Features

- Integrated Control Panel
- OSD With Multi-Language Support
- Wall Mount VESA Compliant (75 x 75 mm)



Typical Applications

- Aerospace
- Commercial
- Defence
- Industrial Consoles
- Marine Consoles
- Medical Systems
- Military
- OEM
- Radar Applications
- System Integrators

Product Description

The DM-15W2-OF 15.4" Widescreen Open Frame LCD Display has a host of features including OSD With Multi-Language Support ,Wall Mount VESA Compliant (75 x 75 mm), to name a few. Designed and built to survive harsh conditions and are perfectly suited for Aerospace , Commercial , Defence , Industrial Consoles , Marine Consoles , Medical Systems , Military , OEM , Radar Applications , System Integrators and other demanding applications. The typical lifetime of an DM-15W2-OF 15.4" Widescreen Open Frame LCD Display is approximately 50,000 hours (typ).



Technical Specifications

SKU	DM-15W2-OF
Weight	4.5000
Manufacturer	FBP
Country of Manufacture	Taiwan
Screen size	15.4"
Mounting Type	No
IP Rating	No
Screen Technology	LCD
Aspect Ratio	16:10
Display Resolution	1440 x 900
Backlight Life	50,000 hours (typ)
Viewing Angle	140 degree in horizontal & 120 in vertical (typ)
Frequency Range	Fh: 30 to 82Khz, Fv: 60 to 75Hz
Brightness	450 cd/m2
Response Time	< 8 ms (G-to-G)
Contrast Ratio	400:01:00
Pixel Dimension	0.23 (H) x 0.23 (V) mm
OSD Control	No
Connectivity	15 Pin female D-Sub x 1, Stereo headphone jack x 1, 12 VDCJack
Video Signal	Analog RGB (0.7/1.0 Vp-p, 75 ohms)
Sync. Signal	Separate Sync, Composite Sync, Sync on Green
Power - Input Voltage	Universal/ Auto-sensing, 90 to 260VAC, 50/60 Hz
Power Consumption	Operation 28 Watt (Max) Stand-by < 1 Watt
Temperature Range	OPERATING: 0C to +40C / STOREAGE: -20C to +60C
Weight	4.5 Kg (N.W.) / 5.5 Kg (G. W.)
Certifications	CE
Accessories Included	AC/DC Power Adapter
Model Number(s)	DM-15W2-OF

Warranty 1 Years RTB Warranty

Availability 3-5 Weeks

