

FPD100833

Main Features

- Protective Anti Reflex Glass
- 1280 x 1024 Display Resolution
- OSD With Multi-Language Support
- Wall Mount VESA Compliant
- 3 Year Standard Warranty
- Option for Integrated MSR, Speakers
- Option for Custom Logo and Case Colour

Typical Applications

- Aerospace
- Commercial
- Defence
- Digital Signage
- Industrial Consoles
- Marine Consoles
- Medical Systems
- Military
- OEM
- Point Of Sale
- System Integrators

Product Description

With the MultiQ 219, MultiQ have taken custom made monitor solutions for retail and public environments one step further. The MultiQ 219 is a 19? solid, stable and very flexible display screen combined in a compact and elegant design. Metal housing and

F B Peripherals Limited, Alva House, Valley Drive, Gravesend, Kent, DA12 5UE, United Kingdom
TEL: +44(0) 203 070 3334 :: EMAIL: support@fbperipherals.com :: WEB: www.fbperipherals.com

Technical Specifications

SKU	FPD100833
Weight	0.0000
Manufacturer	MultiQ
Country of Manufacture	Sweden
Screen size	19"
Mounting Type	VESA
IP Rating	No
Housing Material	Metel
Screen Technology	LED
Aspect Ratio	No
Power Management	DPMS Compatible, Energy Star
Display Resolution	1280 x 1024
Backlight Life	50,000 hours (typ)
Viewing Angle	(CR 10:1) H: -89 degree - 89 degree (Typ.) (CR 10:1) V: -89 degree - 89 degree(Typ.)
Brightness	300 cd/m2
Response Time	8 ms GTG (Typ.) 20 ms Tr+Tf (Typ.)
Contrast Ratio	1500:1 (Typ.)
Pixel Dimension	0,294 (H) x 0,294 (V) mm
OSD Control	No
Connectivity	VGA (15-pols D-sub), DVI-D (24-pols), DC-In, Composite video, S-video
Video Signal	VGA: Analog 0,7 Vp-p. 75 ohm. DVI: REV 1.0 Digital Single T.M.D.S (Transition Minimised Differential Signaling). AV/S-Video: 1 Vp-p. (0,7 V video + 0,3 V sync.), 75 ohm.
Sync. Signal	TTL Level, Positive/Negative, Separate sync (VGA)
Power - Input Voltage	Input: AC 100~240 V, 50~60Hz Output: +12 V DC, 5.0 A
Power Consumption	40W (Typ.)
Temperature Range	OPERATING: 0C to +40C
Mounting Options	VESA

F B Peripherals Limited, Alva House, Valley Drive, Gravesend, Kent, DA12 5UE, United Kingdom
TEL: +44(0) 203 070 3334 :: EMAIL: support@fbperipherals.com :: WEB: www.fbperipherals.com

Weight	7,5 kg With Vesa
Certifications	Safety: UL, EMI: CE/FCC, ISO 13406-2, CCC, CEC approved power supply.
Accessories Included	AC/DC adapter - 1,5 m (black), Power cord - 1,5 + 1,5 m (black), VGA cable - 1,8 m (black). OPTIONS Touch: Serial or USB cable - 1,8 m (black).
Model Number(s)	FPD100833
Warranty	3 Years RTB Warranty
Availability	1-2 Weeks

F B Peripherals Limited, Alva House, Valley Drive, Gravesend, Kent, DA12 5UE, United Kingdom
TEL: +44(0) 203 070 3334 :: EMAIL: support@fbperipherals.com :: WEB: www.fbperipherals.com