


PM-5K

DATE	CHANGES	INTL	REV
12.17.03	Original		1.0
09.09.08	Updated format	JB	1.0
03.18.10	Added stud length (PG1 and PG2)	JB	2.0



KEY SWITCH

MATERIAL: Industrial Silicone Rubber
LIFE: Greater Than 10 Million Cycles
TRAVEL: 0.055 in.
ACTUATION FORCE: 7.03 oz. +/- 1.06oz (200g +/- 30g)
FEEDBACK: Tactile with Mechanical Snap

POWER

PS2 or AT/Serial:
KEYBOARD: 50mA@5V (from Keyboard port)
POINTER: 35mA@5V (from Mouse port)
USB: 85mA@5V (from CPU port)

TEMPERATURE RANGE

STORAGE: -40°F to +158°F (-40°C to +70°C)
OPERATING: -4°F to +140°F (-20°C to +60°C)

HUMIDITY

100% Humidity Resistant

VIBRATION

POWER SPECTRAL DENSITY: .04g²/HZ
FREQUENCY RANGE: 20Hz-2Khz
DURATION OF TEST PER AXIS: 3 hours

SHOCK

3 X 11 ms pulses of 50g on each of 3 axis

WEIGHT

5.25 lbs +/- 0.10 lbs (2.38 kg +/- 0.05 kg)

PROPRIETARY AND CONFIDENTIAL

SCALE: 1:2.5



iKey, Ltd.
 2621 Ridgpoint Dr. Suite 235
 Austin, Texas 78754

©2010 iKey, Ltd.

Voice: (512) 837-0283
 Fax: (512) 927-8630

Part Number: PM-5K

Drawing Title: PM-5K-MKT

Drawing Number: MKT0019



Revision: 2.0

Sheet: 1 OF 2

Date: 03.18.10

JWB

PM-5K BACK / MOUNTING



ENCLOSURE CASE: Stainless Steel

1. PLACE UNIT IN 7.9\"X16.4\" CUT PIT
2. PLACE 4 BRACKETS ON EACH SIDE AND HAND TIGHTEN LOCKING HEXNUTS OVER ALL 14 8-32x0.75\" STUDS
3. TIGHTEN WITH TORQUE WRENCH (15 IN.LB.) IN ORDER SHOWN (1-14) ABOVE

PROPRIETARY AND CONFIDENTIAL

SCALE: 1:2.5



iKey, Ltd.
2621 Ridgpoint Dr. Suite 235
Austin, Texas 78754

©2010 iKey, Ltd.
Voice: (512) 837-0283
Fax: (512) 927-8630

Part Number: PM-5K

Drawing Title: PM-5K-MKT

Drawing Number: MKT0019

Revision: 2.0

Sheet: 2 OF 2

Date: 03.18.10

JWB